

400A Series IP67

IEC 60309-1 IEC 60309-2
GB/T11918.1

	Amp.	400	Plug • With cable clamping plates • IP rating: IP67 ▲▲
	Poles	4/5	
	a	470.2	
	b	247	
	c	391.2	
	d	358.2	
	Min wire size(mm ²)	70mm ²	
	Max wire size(mm ²)	185mm ²	
	Cable outer diameter range	ø45~ø66	

	Amp.	400	Socket • IP rating: IP67 ▲▲ • Flange: 127.2mmX127.2mm
	Poles	4/5	
	a	127.2	
	b	127.2	
	c	212.4	
	d	217.2	
	e	90	
	f	248	
	h	ø154	
	j	ø7	
Min wire size(mm ²)	70mm ²		
Max wire size(mm ²)	185mm ² 240mm ²		

	Amp.	400	Connector • With cable clamping plates • IP rating: IP67 ▲▲
	Poles	4/5	
	a	516.2	
	b	358.2	
	c	217.3	
	d	242	
	Min wire size(mm ²)	70mm ²	
	Max wire size(mm ²)	185mm ²	
	Cable outer diameter range	ø45~ø66	

	Amp.	400	Plug • With cable clamping plates • IP rating: IP67 ▲▲
	Poles	4/5	
	a	261.4	
	b	10°	
	c	451	
	d	65.2	
	e	140	
	f	182	
	g	11	
	h	140	
j	178		
k	217.2		
Min wire size(mm ²)	70mm ²		
Max wire size(mm ²)	185mm ²		
Cable outer diameter range	ø45~ø66		



415V
50-60Hz

Amps

Poles

5 poles
6h

Pack unit

Net weight

A

P

TYP

pcs/package

g/pcs

	400	4	754146	1	8555
	400	5	754156	1	9176


	400	4	754246	1	5514
	400	5	754256	1	6092

	400	4	754346	1	9655
	400	5	754356	1	10233

	400	4	754546	1	10500
	400	5	754556	1	11100

400A Series IP67


IEC 60309-1 IEC 60309-2
GB/T11918.1



Amp.	400
Poles	4/5
a	179.7
b	10°
c	405
d	65.2
e	140
f	182
g	11
h	140
i	247
Min wire size(mm ²)	70mm ²
Max wire size(mm ²)	185mm ²
Cable outer diameter range	ø45-ø66

Plug


- With cable clamping plates
- IP rating: IP67 ▲▲



Amp.	400
Poles	4/5
a	247
b	ø130
c	315
d	10
e	3
f	180
g	155
h	127.2
i	180
j	155
k	127.2
l	4-ø11
Min wire size(mm ²)	70mm ²
Max wire size(mm ²)	185mm ² 240mm ²

Socket

- IP rating: IP67 ▲▲
- Flange:155mmX155mm



Amp.	400
Poles	4/5
a	345.9
b	427.7
c	506.8
d	64.2
e	135°
f	247
g	321.1
h	218.3
Min wire size(mm ²)	70mm ²
Max wire size(mm ²)	185mm ²
Cable outer diameter range	ø45-ø66

Plug

- With cable clamping plates
- IP rating: IP67 ▲▲



415V
50-60Hz

Amps

Poles

5 poles
6h

Pack unit

Net weight

A

P

TYP

pcs/package

g/pcs



400	4	754646	1	10030
400	5	754656	1	10650





400	4	754446	1	7094
400	5	754456	1	7715



400	4	754746	1	8700
400	5	754756	1	9300



IEC 60309-1 IEC 60309-2
GB/T11918.1

400A Series IP67





Amp.	400
Poles	4/5
a	15
b	15°
c	5
d	247
e	191,61
f	120
g	ø11
h	R10
i	120
j	155
k	155
Min wire size(mm²)	70mm²
Max wire size(mm²)	185mm² 240mm²

- Socket**
- IP rating: IP67 ▲▲
 - Flange: 180mmX180mm



Amp.	400
Poles	4/5
a	295
b	30°
c	15
d	5
e	217,3
f	212,4
g	175,25
h	170
i	ø11
j	151
k	170
最小穿线截面积(mm²)	70mm²
最小穿线直径(mm)	
最大穿线截面积(mm²)	185mm² 240mm²
最大穿线直径(mm)	

- Socket**
- IP rating: IP67 ▲▲
 - Flange: 200mmX200mm



Amp.	400
Poles	4/5
a	15°
b	15
c	5
d	212,42
e	217,26
f	120
g	ø11
h	120
i	R10
j	155
k	155
Min wire size(mm²)	70mm²
Max wire size(mm²)	185mm² 240mm²

- Socket**
- IP rating: IP67 ▲▲
 - Flange: 180mmX180mm



415V
50-60Hz

Amps

Poles

5 poles
6h

Pack unit

Net weight

A

P

TYP

pcs/package

g/pcs



400	4	TYP754A46	1	7680
400	5	TYP754A56	1	8300



400	4	TYP754846	1	7480
400	5	TYP754856	1	8050



400	4	TYP754946	1	8180
400	5	TYP754956	1	8750